

SAFETY MEETING

Company Name: Superior Waterproofing

Tool Talk #16

Date: 4/30/2021

Important Information about Fall Protection

1. According to OSHA, fall protection is required when a fall hazard exists that is ____ feet or more above a lower level. a. 4 **b. 6** c. 10 d. 30
2. An example of primary fall protection is:
a. A 36 inch guardrail b. A hole cover c. Balance d. Personal Fall arrest Equipment
3. Secondary fall protection is considered to be _____ primary fall protection.
a. Optional to **b. Backup to** c. Used in place of d. More expensive than
4. Personal fall arrest is used when: (more than one answer)
a. Your supervisor requires it
b. You decide it is necessary
c. A fall exposure can't be protected with a guardrail or safety net
d. When OSHA rules require it
5. What is the minimum clearance required when using a 6 foot energy absorbing lanyard, anchored at D ring height?
a. 6 b. 12 ½ **c. 15 ½** d. 20
6. If a worker is working on a 10 foot roof which of the following should be used?
a. 6ft lanyard attached to a harness **b. retractable lifeline attached to a harness**
7. The back D-ring of a full body harness is positioned properly when it is located _
a. Center of back b. Even with back of neck c. Waist level
d. Between shoulder blades
8. A lifeline anchor point must be able to hold _____ lbs.
a. 900 b. 1800 **c. 5000** d. 10,000
9. Your fall protection system should be inspected _____.
a. Weekly b. Each month c. At least yearly **d. Before you use it**
10. Fall protection should be stored in a dry place out of the sun.
True or False

WHAT UNSAFE OPERATIONS DID YOU FIND ON YOUR JOBSITE THIS WEEK? _____

What Corrective action was taken? _____

Meeting Attended By _____

Supervisor's Signature _____